

- 4 -

What is claimed is:

1. A method for fabricating an optocoupler, the method comprising:
disposing a shield on a photodiode, wherein the shield is configured to prevent electrical
5 fields from reaching the photodiode, and wherein the shield includes one or more apertures
through which light can pass to the photodiode; and
enclosing a light emitting diode with the photodiode and the shield inside a device
package such that light generated by the light emitting diode travels through an inner space
defined by the device package to the photodiode for detection.
10
2. The method of claim 1, further comprising:
fabricating the photodiode in a semiconductor structure.
3. The method of claim 2, wherein:
15 disposing the shield on the photodiode includes depositing one or more electrically
conductive elements over a portion of a surface of the semiconductor structure.
4. The method of claim 3, wherein:
depositing one or more electrically conductive elements includes depositing one or more
20 conductive materials over a portion of the surface of the semiconductor structure, wherein the
conductive materials include one or more of aluminum, copper, gold, silver, polysilicon, and a
silicide.
5. The method of claim 3, wherein:
25 depositing one or more electrically conductive elements includes depositing the
electrically conductive elements as a portion of a metallic interconnect layer.
6. The method of claim 3, wherein:

- 5 -

depositing one or more electrically conductive elements includes depositing a conductive layer having a thickness of about 100 Å to about 20,000 Å.

7. The method of claim 3, wherein:

5 depositing one or more electrically conductive elements includes depositing electrically conductive elements having a line width that is between about 0.2 μm and about 1 μm.

8. The method of claim 1, wherein:

10 disposing a shield on a photodiode includes disposing a shield including electrically conductive elements that define a grid, a series of parallel lines, concentric circles, or a spiral.

9. The method of claim 1, wherein the device package includes electric leads, the method further comprising:

15 electrically connecting the photodiode or the light emitting diode to the electric leads of the device package.

10. A method for operating an optocoupler, the method comprising:

converting an input electric signal into light using a light emitting diode enclosed inside a device package;

20 transmitting the light inside an inner space defined by the device package from the light emitting diode through one or more apertures in a shield to a photodiode enclosed inside the device package; and

converting the transmitted light into an output electric signal using the photodiode.

25 11. The method of claim 10, wherein the photodiode is included in a semiconductor structure.

12. The method of claim 11, wherein:

transmitting light through one or more apertures in a shield includes transmitting light through one or more apertures in a shield that includes one or more electrically-conductive elements deposited over a portion of a surface of the semiconductor structure.

5 13. The method of claim 11, wherein:

transmitting light through one or more apertures in a shield includes transmitting light through one or more apertures in a shield that includes electrically conductive elements in an interconnect layer of the semiconductor structure.

10 14. The method of claim 10, wherein:

transmitting light through one or more apertures in a shield includes transmitting light through one or more apertures in a shield including electrically conductive elements that define a grid, a series of parallel lines, concentric circles, or a spiral.

15 15. The method of claim 10, further comprising:

using the shield to terminate electrical fields from the light emitting diode before reaching the photodiode.

16. The method of claim 15, wherein:

20 using the shield to terminate the electrical fields includes connecting the shield to a potential source.

17. The method of claim 16, wherein:

25 connecting the shield to a potential source includes connecting the shield to ground potential.

18. The method of claim 10, further comprising:

receiving the input electric signal through an electric lead of the device package.